

6072q Series Thin Clients

Industry Leading Endpoints & Management Software

The Nutanix Frame Ready 10ZiG 6072q is a powerful Thin Client workhorse series. Its small-footprint design features an Intel Quad Core 1.5GHz (2.5GHz Burst) processor and is powered by PeakOS™, 10ZiG’s purpose-built, Linux-based custom Thin Client OS. Engineered for performance, security, simplified configuration, and management for Cloud Workspaces and Virtual Desktops, this endpoint features the Nutanix Frame Linux App; is compact, durable, reliable, fanless; and features 4K UHD support, USB Port C, Wireless Option, and TAA Compliance. The 6072q comes equipped with free centralized management via the cloud-enabled 10ZiG Manager™ with unlimited user licenses and, is covered by a 3-Year Advance Warranty, Technical Support, and Software Upgrades.



| |
|--|
| ▶ Intel Quad Core 1.5GHz (2.5GHz Burst) |
| ▶ 2 x DisplayPort (3840 x 2160), 4K @ 60Hz |
| ▶ Up to 8GB DDR4 RAM for High Speed Support |
| ▶ 4 x USB Port 2.0, 1 x USB Port 3.0, 1 x USB Port C |
| ▶ RJ45 LAN/Fiber (SFP) Ready Options |
| ▶ Optional TPM 2.0 |
| ▶ TAA Compliant |
| ▶ Optional Wireless (Dual External Antenna) |
| ▶ Supports VESA Mount and Kensington Lock |
| ▶ FREE Centralized Management via 10ZiG Manager™ |

6072q Series Thin Clients



| System | |
|---------------------|--|
| Management | 10ZiG Manager™ |
| RAM | Std: 4GB, Max: 8GB |
| Storage | Std: 8GB, Max: 256GB |
| Processor | Intel Quad Core 1.5GHz (2.5GHz Burst) |
| Processor Graphics | Intel HD Graphics |
| Dimensions | |
| Device | 1.7" (D) x 6.0" (W) x 7.9" (H) in. |
| Weight | 3.53 lbs. (1.6 kg.) |
| Connections | |
| Ports on Device | 2 x DisplayPort, 4 x USB Port 2.0, 1 x USB Port 3.0, 1 x USB Port C, 1 x Mic-In, 1 x Line-Out, 1 x DC Jack |
| Port-on-Foot Option | 1 x COM + 1 x Parallel Port |
| Video Resolution | 2 x (3840 x 2160) @ 60Hz (2 Monitors at 4K UHD) |
| Networking | |
| Wireless | Optional (802.11 a/b/g/n/ac External Antenna) |
| Ethernet | 10/100/1000 Base-T, RJ45 LAN or Fiber LAN (SFP) Optional |
| Environmental | |
| Operating Temp. | 32°-95°F (0°-35°C), 20-80% non-condensing humidity |



SPECIFICATIONS

- | | |
|---------------------------|-----------------------------------|
| 1. Power Button/Power LED | 7. USB 2.0 |
| 2. USB Type C | 8. DisplayPorts |
| 3. USB 3.0 | 9. RJ45 LAN/Fiber LAN (SFP Ready) |
| 4. Mic-In | 10. 12V DC Jack |
| 5. Line-Out | 11. Kensington Lock Slot |
| 6. Antenna Holes | 12. Optional Port-on-Foot |

Note: Actual display performance, such as multi-monitor and higher resolutions including 4K/UHD/QHD/WQHD are dependent upon your current VDI infrastructure and any additional requirements. Consult with 10ZiG for further guidance and model recommendation.

*Optional Application may require alternative model; please speak to a sales representative to confirm.

Americas P: +1 (866) 865-5250
 EMEA P: +44 (0) 116 214 8650
 APAC P: +61 2 80027421
 DE P: +49 (0) 6724 9304-45

E: info@10ZiG.com
 E: info@10ZiG.eu
 E: info@10ZiG.com.au
 E: vertrieb@10zig.de

W: www.10ZiG.com

